



POLY ELAST RAPID-O



POLY ELAST RAPID-O is a single layer universal bituminous membrane that has been specially formulated to offer robust performance, versatile installation and value for money.

The robust, 6kg/m² membrane provides a cost-effective, fast-track method of overlaying existing roof coverings to provide a reliable, long-lasting waterproofing solution. It can also be used as a high performance, single-layer cap sheet in warm roof specifications.

GRAPHITE FIREWALL TECHNOLOGY

POLY ELAST RAPID-O incorporates graphite firewall technology which actively prevents spread of flames on the roof should a fire occur. In addition, its inherent flexibility allows for effective application in a wide range of temperatures and gives the product innovative self-healing properties.

FAST-TRACK VERSATILE INSTALLATION

POLY ELAST RAPID-O not only offers flexibility in performance, it also provides flexibility in application.

In overlay situations, the membrane can be quickly and easily torch applied onto a wide range of noncombustible substrates. Should client preference or project requirements dictate that naked flames are prohibited on site, the product can either be adhesive bonded or can be simply installed using a heat gun.

Where **POLY ELAST RAPID-O** is being used as part of a full warm roof system, it can be securely bonded to the insulation using an approved PU Adhesive.

KEY BENEFITS OF POLY ELAST RAPID-O

- Ideal for cost-effective, fast-track roof refurbishment
- Effective overlay solution for revitalising and waterproofing existing tired roofs
- Incorporates graphite firewall technology for the ultimate in fire protection
- Diamond shaped channels on underside providing reliable, strong bond and roof moisture control
- Versatile methods of installation
- Robust, thick product highly resistant to site traffic
- Can be torched to suitable non-combustible substrates
- Available with a 20 year materials guarantee
 - 1. POLY ELAST RAPID-O Single Layer Universal Membrane
 - 2. Existing roof surface (e.g. asphalt or bituminous waterproofing membrane)

EFFECTIVE ROOF MOISTURE CONTROL

The unique design of POLY ELAST RAPID-O means that it is far more than just a waterproofing solution.

The highly advanced membrane features rapid torch-on points on the underside which provide a reliable, strong bond to the substrate, whilst also allowing vapour pressure from the roof to be effectively equalised and controlled.

Innovative diamond-shaped torch-on points on lower surface of membrane

VERSATILE PERFORMANCE



Fire Protection Waterproofing

Moisture Control

VERSATILE APPLICATION



Torch-Applied Hot Air Welded PU Adhesive Bonded





INSURANCE

BACKED

GUARANTEE

Superglass Insulation Limited Thistle Industrial Estate, Kerse Road, Stirling, FK7 7QQ www.tnroofingsystems.com info@tnroofingsystems.com Tel. 01786 451170