

StrataPlan Seam Sealant

PVC liquid sealant for use within Strataplan PVC systems

Product overview

StrataPlan Seam Sealant is designed to be used in conjunction with StrataPlan PVC membranes. It can be used to create the look of one homogenous membrane.

Application guidelines

Ensure that all surfaces are dry and free from dirt, oil, grease, or other contaminants. If necessary, clean the surfaces thoroughly. Verify that the sealant is maintained at a temperature between 12°C and 30°C to ensure optimal adhesion.

Stir the sealant well before use, and take care to prevent water from contaminating it. Apply the sealant to seams exclusively using a specialised applicator to ensure an even and consistent coverage.

Technical characteristics

Properties	Declared Performance
Appearance	Anthracite (RAL7016)
Base	Tetrahydrofuran
Flammability	Highly flammable
Shelf life	12 months

Handling & storage

To ensure optimal performance, StrataPlan Seam Sealant should be stored in well-sealed containers for a maximum of 12 months. It is important to avoid both low and high temperature storage; the adhesive should ideally be kept between 12°C and 30°C. Additionally, due to the presence of highly flammable solvents, it is imperative that the sealant is stored in dry, well-ventilated areas.

Environmental considerations

Dry residues may be disposed of as industrial waste. Liquid residues should be disposed of as hazardous waste.

Health and safety

Health and Safety should be observed at all times in accordance with HSE and industry guidance. Specific Risk Assessments and Method Statements should be produced by contractors where necessary to ensure Working at Heights, Fire Safety and Manual Handling rules are compliant with current law and regulations. A material safety datasheet is available for this product upon request.

Further information

The information contained in this datasheet, along with any advice provided (either written or verbal) through testing are based on our experience and do not constitute any product guarantee for the installer.

We recommend that all of the information provided is carefully studies before proceeding with application, and strongly advise that suitable tests are carried out on site before application in order to determine the suitability and compatibility for the specific project.

The application, use and processing of our products are beyond our control, and therefore under the exclusive responsibility of the installer. As a result, the installer will be solely responsible for any damage derived from the partial or complete disregard of our guidance or the general mis-use of any of our materials.